37-226.2 (3-16)

Allegion NL B.V. - Energiestraat 2 - 3903 AV Veenendaal - Nederland - info.axa.home@allegion.com - axahomesecurity.com




AXA HOME/SECURITY

Adapter for the AXA Remote 2.0

Information

You have just acquired a high quality AXA product. The instructions below must be followed closely in order to effectively install and operate this product.

Application:
AXA Remote 2.0



Installation manual

1. Install the closing unit as shown in the assembly manual accompanying the AXA Remote 2.0.

2. Remove the battery before connecting the adapter to the closing unit and the mains (230 V) (figure **A**).

3. Decide if you want the adapter wire to come out the left or right side of the closing unit (depending on the location of the power socket).
Use cutters to cut a small snippet from the cover in the semi-perforated area (figure **B**) on the side chosen.

4. Click the adapter wire into the closing unit (figure **C**):

- lead the wire from the left-hand side of the closing unit (figure **D**)and place the adapter in the power socket.

or:
- lead the wire through the groove (figure **E**) on the right-hand side of the closing unit and under the designated hook (figure **F**).
Push the adapter into the power socket.

Make sure the wire lies neatly along the window frame.

You must still register the remote control after you have connected it to the unit and the mains (230 V).
Follow point punt 2 (registration of remote control of the AXA Remote 2.0) in the installation manual.

Warning: only use the product indoors!

